

	UNIT 7, 11-17 Canvale Road PO BOX 1616 Canning Vale WA 6155 www.locksafe.com.au	ORDERS / ENQUIRIES: PHONE: 08 9455 7255 FAX: 08 9455 7244 info@locksafe.com.au	<b>Gremarnig Holdings          Pty Ltd</b> Trading as <b>Locksafe Industrial          Safety Equipment</b> ABN: 24 109 254 293 ACN: 109 254 293
	ACCOUNTS ENQUIRIES: PO BOX 569 Singleton NSW 2330	Phone: 02 6571 1232 Fax: 02 6571 1368	

*Fitting Instructions for*  
**LS 11006**  
**LS 13030**  
**LS14010**  
**LS14010S**

**(-01 &-02 for both)**

**Lockable Brackets and isolator assemblies to suit  
 The Big Red switch. (2500 amp DC int 150 amp continuous)**

- Remove the original aluminium handle from the Big Red switch by removing the handle pin with a 3mm punch.
  - The handle **must** be supported during this operation to avoid any damage to the switch casing.
  - Fit the Locksafe handle and reinsert the handle pin in the hole provided in the handle, again support body.
  - Turn handle to vertical position and secure the locking bracket to the switch with the switch mounting bolts.
  - The lug **must** be on the left. It may be necessary to trigger the switch 180 degrees around so the handle is positioned correctly.
  - To do this remove the cover on the underside of the switch.(Remove Bracket also)
  - Apply a battery feed to connections #2 & #12 with the switch in the **on** position.  
 You will hear a 'click' this is the internal delay activating the switch off eg: remote shut down
- This applies to the older style big red with the on/off in window, the new led style cannot be activated and turned past the on position once activated. For the new led style switch press the handle into place.**
- Turn the handle 15 degrees to past 'click'. The handle is now set in 180 degrees to previous position and aligns with the handle correctly.
  - Red bracket (-01) to depicts Battery Isolation and yellow for Starter Isolation (-02)

Once installed, always ensure isolation is Effective before commencing work.  
 Switch turned on LED must be on,  
 switch off LED off.  
 Locking bracket 3mm stainless steel  
**NOTE; Isolator Switch failure due to Vibration are not covered under warranty.**

