



UNIT 7, 11-17 Canvale Road  
PO BOX 1616  
Canning Vale WA 6155  
www.locksafe.com.au

ACCOUNTS ENQUIRIES:  
PO BOX 569  
Singleton NSW 2330

ORDERS / ENQUIRIES:  
PHONE: 08 9455 7255  
FAX: 08 9455 7244  
info@locksafe.com.au

Phone: 02 6571 1232  
Fax: 02 6571 1368

**Gremarnig Holdings  
Pty Ltd**  
Trading as  
***Locksafe Industrial  
Safety Equipment***

ABN: 24 109 254 293  
ACN: 109 254 293

*Fitting instructions for*

**LS 11001**

**LS 11002**

**LS 13011**

**LS 13012**

**(-01 & -02 FOR ALL)**

## *Lockable brackets and units to suit the Caterpillar Switch (7n-0718)*

- If switch to be supplied, mount near to the battery as possible, allowing for access for a padlock to the bracket.
- The measurement from the centre hole (20 mm) to the pin holes (7 mm) is 20.5mm. 41 mm to outside centres.
- Remove the switch-retaining nut leaving the switch in its mounting position.
- Slip the locking bracket partially on to the switch boss.
- Thread the Ezy Key thru the switch locking washer and retaining nut and locate the key into the switch slot.
- Ensure the key is correctly positioned and the key retaining bar on the bracket is on the top of the key. It may be necessary to tilt and turn the bracket slightly to facilitate correct fitment.
- Tighten locknut to secure the bracket and switch assembly. Support the switch body when tightening to prevent twisting on the pin.
- If the LED is to be fitted, provide permanent fused positive feed to the red-sheathed wire, and connect the black to the switched side of the master switch. It must turn off when isolated.
- **DO NOT** bend the key retaining bar to facilitate fitting of this device. The preferred panel thickness is 5 - 6mm, any less than this and the key will jam on the inside of the bracket, unless a spacer washer is used between the switch and the inside panel.

*When installed correctly this bracket will permanently retain the key in the switch and will only be able to be locked in the off position.*

*Once installed, always ensure isolation is effective before commencing work.*

*Manufactured from 2mm stainless steel.*

*Patented Quality Locksafe product.*

