

LOCKSAFE
Lock Safe

UNIT 7, 11-17 Canvale Road
PO BOX 1616
Canning Vale WA 6155
www.locksafe.com.au

ORDERS / ENQUIRIES:
PHONE: 08 9455 7255
FAX: 08 9455 7244
info@locksafe.com.au

**Gremarnig Holdings
Pty Ltd**
Trading as
**Locksafe Industrial
Safety Equipment**

ABN: 24 109 254 293
ACN: 109 254 293

ACCOUNTS ENQUIRIES:
PO BOX 569
Singleton NSW 2330

Phone: 02 6571 1232
Fax: 02 6571 1368

Fitting instructions for
LS 11003
LS 13007
LS 13008
LS13009
LS 13010
(-01 & -02 FOR ALL)

Lockable brackets and units to suit the Bosch Switch (0341003004) Double Pole

Hella Switch (4563) 2500 amp 24 v for 10 sec 100 amp cont @ 60 C

- If switch to be supplied, mount near to the battery as possible, allowing for access for a padlock to the bracket.
- The measurement from the centre hole (23 mm) to the boltholes is 100 mm or 120mm to overall outside centres.
- Drill holes and offer switch up. Mount vertically. Clean surfaces front and back of switch position,
- Silicone seal both surfaces to prevent water running down between switch/panel and locking bracket /panel areas.
- Offer the locking bracket up to the switch and engage the plunger into the switch by turning the handle on.
- Ensure handle is located correct way round. Long part of handle at the top.
- Turn body of bracket to align lug into centre of handle. Secure with bolts.
- Depending on panel thickness the handle may be able to rotate 360 deg when in off position, this is OK. Turn handle to lug with hole in to apply padlock. Push in and turn to switch on.
- If the LED is to be fitted, provide permanent fused positive feed to the red-sheathed wire, and connect the black to the switched side of the master switch. It must turn off when isolated.
- Vibration, water and dust are the main reason for unit failure; avoid placing unit in extreme exposure to these.
- Connect battery cables and check operation of unit.
- Red use for battery (-01) and yellow for starter (-02)

***When installed this bracket will
only be able to be locked in the off position.
Once installed, always ensure isolation
is effective before commencing work.
Manufactured mainly from stainless steel.
Patented Quality Locksafe product.***

