



FITTING INSTRUCTIONS

BIG RED SWITCH

LS11006 LS13030 LS14010 LS14010S

Installation

- Remove the original handle from the Big Red switch by removing the handle pin with a 3mm punch.
- The handle must be supported during this operation to avoid any damage to the switch casing.
- Fit the Locksafe handle and reinsert the handle pin in the hole provided in the handle, again support the body.
- Turn the handle to vertical position and secure the locking bracket to the switch with the switch mounting bolts.
- The lug must be on the left. It may be necessary to trigger the switch 180 degrees around so the handle is positioned correctly.
- To do this remove the cover on the underside of the switch. Remove the bracket also.
- Apply a battery feed to connections #2 & #12 with the switch in the ON position. You will hear a 'click', this is the internal delay activating the switch OFF i.e. remote shut down.
- This applies to the older style big red with the ON/OFF in window. The new LED style cannot be activated and turned past the ON position once activated. For the new LED style switch press the handle into place.
- Turn the handle 15 degrees to past 'click'. The handle is now set in 180 degrees to previous position and aligns with the handle correctly.
- Red bracket (-01) to depicts Battery Isolation and yellow for Starter Isolation (-02)

Important Notes

- Once installed, always ensure isolation is effective prior to commencing work.
- Switch turned on LED must be on, switch off LED is off.
- Isolator Switch failure due to vibration is not covered under warranty.